![Jofemar logo]

Jofemar
Vending Machines

Vision Easy Plus

Cover-Front machines manufactured by Jofemar allows to set on sale special products needing a better isolation when machines face the sun or products which cannot be straight displayed, fishing worms, delicate milk products, tobacco…

Includes the EasyFlex system, the most effective way to adapt a vending machine to any kind of product and packaging.

Technical characteristics

- Programmable temperature from 2 ºC to 12º C with different temperature areas, three points temperature division inside the cabinet.
- Capacity of up to 8 fully adjustable trays and up to 10 channels each.
- FIFO system used to deliver products.
- Vend detection by photocells.
- Leds lightening system with on-off programming.
- Auto - self diagnostic control system.
- Health timer that inhibits vends of out - of -date products.
- Flexible configuration. The easyFlex system allows the fast modification of the width and depth of the channel. No additional spare parts are needed to create a new configuration
- Programmable torque and speed of the motors.
- Power Supply: 220-240 VAC (Optional 110 V.)
- Maximum consumption 650w

Dimensions and weight

- Dimensions: 1825 x 800 x 935 mm
- Weight: 297 Kg.

Structure

- Robust construction with an anti-corrosive and antioxidation coating material
- Security lock with 3 locking points
- Cash box of high capacity and with the optional accessories of self-locking when removed from the base.

- Injected foam on all the cabinet, assures the best refrigeration using lower power consumption by the cooling unit.

Cash-credit management

- Vending protocols MDB or Executive.
- Change giver with 5 tubes for more flexible change combination.
- Advanced coin validator with the most reliable systems to detect frauds and fake coins.

Programming and management

- On site programming facilities with in built modules.
- Cloning machine options with handheld device.
- Remote programming, data extraction, out of product alarm on real time, and more options using Jofemar telemetry software "Vending Track"
- Data retrieval for audits and statistics.
- RS232 data output.

Options

- Bill Validator BT10
- Cashless payment system J130
- Vandal- proof coins entry.
- Modem interface for telemetry management.
- Online working mode with full control of sales and users.
- Up to two satellite vending units for extra selections and capacity
- Microwaves tower, ovens and heating times availability controlled by the main Vision Machine